

# AE POWERPLUS MODULE

AE P6-72 Series 300W-325W




ILLUSTRATION ONLY



We produce with green energy!



## GERMAN QUALITY

AE Solar photovoltaic modules are manufactured using high-quality materials, automated machine, German Technology and Standards



## PERFORMANCE GUARANTEE

AE Solar assures high investment, security and warranty claims by providing linear performance guarantee of 30 years and 12 years of product warranty



## POWER RANGE

Plus-Sorting 0 to + 4,99Wp



## PID RESISTANT

Potential Induced Degradation Free



## SALT CORROSION RESISTANT

Certified for Salt Rich Environment



## SAND RESISTANT

Certified for Sand Rich Environment



## AMMONIA RESISTANT

Certified for Ammonia Rich Atmosphere



## HIGHLY STABLE AND TOUGH

Maximum Mechanical Load 5400 Pa



## PLUS-SORTING


Higher yield due to plus-sorting of 0 to +4.99 Wp guarantees the high system efficiency and yield stability



## CERTIFICATES

Lining with International Standards, AE Solar Photovoltaic modules are tested and certified under extreme stress and it can bear harsh environmental influences

## OUR PERFORMANCE GUARANTEE



IEC 61215  
IEC 61730  
PERIODICAL  
INCEPTION



IEC 61215  
IEC 61730  
PERIODICAL  
INCEPTION



PID RESISTANT  
SALT MIST RESISTANT  
SAND RESISTANT  
CORROSIVE GAS (NH<sub>3</sub>)



### ELECTRICAL DATA


		AE300P6-72	AE305P6-72	AE310P6-72	AE315P6-72	AE320P6-72	AE325P6-72
Nominal power	Pm (Wp)	300	305	310	315	320	325
Open circuit voltage	Voc (V)	45.23	45.38	44.47	45.59	45.72	45.83
Short-circuit current	Isc (A)	9.07	9.13	9.17	9.24	9.28	9.33
Voltage at max power	Vmp (V)	36.43	36.51	36.60	36.66	36.75	36.83
Current at max power	Imp (A)	8.23	8.35	8.47	8.59	8.71	8.82
Filling Factor	(%)	73.13	73.61	74.35	74.78	75.42	76.00
Module Efficiency	(%)	15.46	15.72	15.98	16.23	16.49	16.75
System Voltage	(V)	1000					
Temp. coefficient Voc	(%/°C)	-0.35					
Temp. coefficient Isc	(%/°C)	0.06					
Temp. coefficient Pm	(%/°C)	-0.42					
Operating temp.	(°C)	-40 to +85					
NOCT	(°C)	45±2					

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m<sup>2</sup> with spectrum AM 1.5 and a cell temperature of 25°C.

### TECHNICAL DATA

Junction box	3 bypass diodes, IP 67
Wire cross section (∅, mm <sup>2</sup> )	4.0
Cable length (mm)	900 or 1100
Connector type	MC 4 / MC 4 compatible
Dimensions (L x W x H, mm)	1956 x 992 x 40
Weight (kg)	23.5
Specification (mm)	Poly 156 / 6 x 12
Hail resistance	Max. ∅ 28 mm, at 23 m/s
Wind load	2400Pa / 244kg / m <sup>2</sup>
Mechanical load	5400Pa / 550kg / m <sup>2</sup>

### SCALE



### PACKAGING INFORMATION

Packing configuration	54pcs / pallet
Loading Capacity	648pcs / 40HQ
Size / pallet (mm)	1990 x 1120 x 2335
Weight	1380kg / pallet

