



Single-Phase Hybrid Inverter



X1-VAST

5kW / 6kW / 8kW / 10kW



Flexible Expansion

- Dual battery ports and 2-in-1 function for effortless expansion
- Additional ports for simplified wiring and installation
- Functional and stylish wiring cover
- Microgrid and generator modes for versatile operations



Smart Energy

- V2G/V2H ready for smart home energy integration
- Intuitive management with Smart Schedule, Scene, and TOU
- VPP ready, supporting FCAS, 2030.5, and OpenADR.
- Wireless meter compatible for convenient setup



Safe and Reliable

- 10s 200% EPS output with <10ms UPS level switch time
- Support whole-home load without extra devices required
- SPD-II protection on both DC/AC, AFCI optional



Economically Efficient

- 20A DC input per MPPT with 4 trackers
- 200% PV oversizing and Power Input Capacity
- Low PV Start-Up voltage of 40V

X1-VAST-5K

X1-VAST-6K

X1-VAST-8K

X1-VAST-10K

INPUT PV				
Max. PV input power [Wp]①	10000	12000	16000	20000
Max. DC voltage [V]		600		
Normal DC operating voltage [V]		360		
Max. input current (per MPPT) [A]	20 / 20 / 20		20 / 20 / 20 / 20	
Max. short-circuit current (per MPPT) [A]	25 / 25 / 25		25 / 25 / 25 / 25	
MPPT operating voltage range [V]②		40 - 560		
Start output voltage [V]		50		
No. of MPP trackers / Strings per MPP tracker	3 / 1		4 / 1	
OUTPUT / INPUT AC				
Rated grid voltage (AC voltage range) [V]		220 / 230 / 240		
Rated grid frequency [Hz]		50 / 60		
Normal AC output power[W]	4999	6000	8000	9999
Max. apparent AC output power [VA]	4999	6000	8000	9999
Max. AC output current [A]	21.8	26.1	34.8	43.5
Max. apparent AC input power [VA]		14500		
Max. AC input current [A]		63		
Displacement power factor		0.8 leading to 0.8 lagging		
Total harmonic distortion (THD _i , rated power) [%]		< 2		
EPS (OFF-GRID OR BACK-UP) OUTPUT				
Off-grid Nominal voltage [V]; Frequency [Hz]		230; 50 / 60		
Off-grid rated power [VA]	5000	6000	8000	10000
Off-grid rated current [A]	21.8	26.1	34.8	43.5
Off-grid peak power		2 times of Off-grid rated power, 10s		
Total harmonic distortion (THD _v , linear load) [%]		< 2		
Switch time [ms]		< 6		
BATTERY				
Battery voltage range [V]		80 - 480		
Max. charge / discharge current [A]		50 (25 / 25)		
V2G / V2H				
Operating voltage range [V]		360-480		
Operating current [A]		30		
Communication interface		CAN		
EFFICIENCY				
Max. MPPT efficiency [%]		99.9		
Max. efficiency [%]		97.6		
Max. Battery charge/discharge efficiency [%]		97.0		
PROTECTION				
Anti-islanding protection		Yes		
DC reverse polarity protection		Yes		
Insulation monitoring		Yes		
Residual current monitoring		Yes		
AC overcurrent protection		Yes		
AC short-circuit protection		Yes		
AC overvoltage protection		Yes		
Over-heat protection		Yes		
Surge protection		Type II, DC and AC		
Battery reverse charging from grid		Yes		
AFCI		Optional		
GENERAL DATA				
IP class		IP66		
Operating temperature range [°C]		-35 ~ +60 (derate @ 45°C)		
Humidity [%]		4 ~ 100 (condensing)		
Altitude [m]		< 3000		
Typical Noise emission [dB]		< 35		
Cooling concept		Nature convection		
Topology		Transformerless		
Communication	CT, Meter (optional), External control RS485, Pocket WiFi + LAN (Optional: Pocket WiFi 3.0/Pocket WiFi 4G), DRM, USB Upgrade			
Dimensions (W x H x D) [mm]		590 x 400 x 180		
Net weight [kg]		30 ± 2		
STANDARD				
Safety		EN / IEC62109 -1 / -2		
EMC		EN61000-6 -1 / 2 / 3 / 4; EN61000-3 -2 / 3 / 11 / 12		
Certification	AS / NZS 4777, G99, EN 50549-10, BR140, IEC61727, IEC 61683, RD1699, NRS 097-2 -1, PEA / MEA, VFR2019			

①The maximum input voltage is the upper limit of the DC voltage. Any higher input DC voltage would probably damage inverter

②Input voltage exceeding the operating voltage range may trigger inverter protection

*V1.0. Information may be subject to modify without notice.